


EX PROOF FLEXIBLE CONDUIT



- материал : нержавеющая сталь
- стандарт : EN60079
- Stainless steel core (AISI316L)
- Fittings and braiding wire are made of stainless steel SS304
- Extremely small bending radius
- High flexibility
- Female - Female
- ATEX
- II 2G Ex e IIC Gb ; I M2
- II 2D Ex tb IIIC Db, IP66/67

Технические характеристики



| | | |
|------|-------|-------|
| IP67 | -20 C | +80 C |
|------|-------|-------|

| Код продукта | Размер I | Размер II | A | B | C | D | E | F | Вес нетто (кг/шт) | Количество в |
|---------------|----------|-----------|-------|-------|------|---------|---|---|-------------------|--------------|
| VSX816-0100FF | NPT 1/2" | NPT 1/2" | 12.00 | 18.00 | 3.00 | 1000.00 | | | 0,340 | 20.00 |
| VSX816-0150FF | NPT 1/2" | NPT 1/2" | 12.00 | 18.00 | 3.00 | 1500.00 | | | 0,450 | 20.00 |
| VSX816-0200FF | NPT 1/2" | NPT 1/2" | 12.00 | 18.00 | 3.00 | 2000.00 | | | 0,570 | 20.00 |
| VSX821-0050FF | NPT 3/4" | NPT 3/4" | 15.00 | 22.00 | 3.50 | 500.00 | | | | |