


FLEXIBLE STAINLESS CONDUIT, HIGH TEMP,  
STAINLESS BRAIDED



-40 C +150 C

Технически характеристики



| Код продукта | Размер I | A      | B      | C | D | E | Вес нетто (kg/м) | Количество в |
|--------------|----------|--------|--------|---|---|---|------------------|--------------|
| SLA008       | 5/16"    | 8.00   | 13.00  |   |   |   |                  | 50.00        |
| SLA010       | 1/4"     | 10.00  | 15.00  |   |   |   |                  | 50.00        |
| SLA013       | 3/8"     | 12.50  | 18.00  |   |   |   | 0,283            | 50.00        |
| SLA016       | 1/2"     | 16.00  | 22.00  |   |   |   | 0,321            | 50.00        |
| SLA021       | 3/4"     | 20.50  | 27.00  |   |   |   | 0,405            | 50.00        |
| SLA026       | 1"       | 26.50  | 34.00  |   |   |   | 0,636            | 50.00        |
| SLA035       | 1 1/4"   | 35.00  | 43.00  |   |   |   |                  | 30.00        |
| SLA040       | 1 1/2"   | 40.00  | 49.00  |   |   |   | 1,009            | 30.00        |
| SLA052       | 2"       | 51.50  | 60.00  |   |   |   |                  | 20.00        |
| SLA063       | 2 1/2"   | 63.00  | 76.00  |   |   |   |                  | 10.00        |
| SLA078       | 3"       | 78.00  | 91.00  |   |   |   |                  | 10.00        |
| SLA102       | 4"       | 102.00 | 113.00 |   |   |   |                  | 5.00         |