


Infos of FNH :



- IP55
- MIN -25
- MAX 90
- CERT
- FNH

**POLYAMIDE CONDUIT, FLAME RETARDANT V0, BLACK**

- ▶ Polyamide PA6 material
- ▶ High flexibility
- ▶ Polyamide annular corrugated flexible conduit, light, it is extremely flexible with a very low bending radius
- ▶ Resistant to ageing and weathering good oils and acids
- ▶ Halogen-free
- ▶ UV-resistant
- ▶ Self Extinguishing flame retardant UL94 V0
- ▶ Color : Black



Sizes & Prices :

Product Code	Size	Size	A (mm)	B (mm)	C (mm)	D (mm)	Meters in Pack (M)	Net Weight (kg/M)
<b>FNH007</b>	PG7		6.50	10.00	1.75	20.00	100.00	0,022
<b>FNH009</b>			8.50	12.00	1.75	20.00	100.00	0,025
<b>FNH010</b>	PG9		10.00	13.00	1.50	25.00	100.00	0,026
<b>FNH012</b>	PG11		12.00	16.00	2.00	30.00	50.00	0,034
<b>FNH014</b>	PG13.5		14.00	19.00	2.50	35.00	50.00	0,053
<b>FNH017</b>	PG16		16.90	21.20	2.15	40.00	50.00	0,058
<b>FNH019</b>			19.50	24.00	2.75	45.00	50.00	0,000
<b>FNH023</b>	PG21		23.00	29.00	3.00	50.00	50.00	0,090
<b>FNH026</b>			26.00	31.00	2.50	55.00	25.00	0,102
<b>FNH029</b>	PG29		29.00	34.50	2.75	60.00	25.00	0,125
<b>FNH036</b>	PG36		36.00	43.00	3.50	70.00	25.00	0,140
<b>FNH048</b>	PG48		48.00	54.50	3.25	80.00	25.00	0,223

Accessories :

CONDUIT CONNECTOR, POLYAMIDE, GRAY



**F1070**

CONDUIT CONNECTOR, POLYAMIDE, GRAY

TERMINATION BOX, POLYAMIDE, BLACK



**F1600**

TERMINATION BOX, POLYAMIDE, BLACK


POLYAMIDE CONDUIT, FLAME RETARDANT V0, BLACK



**FNH**

POLYAMIDE CONDUIT, FLAME RETARDANT V0, BLACK

POLYAMIDE CORRUGATED CONDUIT, WIRE BRAIDED



**FNX**

POLYAMIDE CORRUGATED CONDUIT, WIRE BRAIDED