




POLYAMIDE CONDUIT, FLAME RETARDANT V0, BLACK

- Polyamide PA6 material
- High flexibility
- Polyamide annular corrugated flexible conduit, light, it is extremely flexible with a very low bending radius
- Resistant to ageing and weathering good oils and acids
- Halogen-free
- UV-resistant
- Self Extinguishing flame retardant UL94 V0
- Color : Black

IP55	-40 C	+120 C
------	-------	--------

Технические характеристики



Код продукта	Размер I	A	B	C	D	E	Вес нетто (kg/м)	Количество в
FV005		5.00	8.00	1.50	20.00			100.00
FV007	PG7	6.50	10.00	1.75	20.00		0,022	100.00
FV009		8.50	12.00	1.75	20.00		0,025	100.00
FV010	PG9	10.00	13.00	1.50	25.00		0,026	100.00
FV012	PG11	12.00	16.00	2.00	30.00		0,034	50.00
FV014	PG13.5	14.00	19.00	2.50	35.00		0,053	50.00
FV017	PG16	16.90	21.20	2.15	40.00		0,058	50.00
FV019		19.50	24.00	2.75	45.00			50.00
FV023	PG21	23.00	29.00	3.00	50.00		0,090	50.00
FV026		26.00	31.00	2.50	55.00		0,102	25.00
FV029	PG29	29.00	34.50	2.75	60.00		0,125	25.00
FV036	PG36	36.00	43.00	3.50	70.00		0,140	25.00
FV048	PG48	48.00	54.50	3.25	80.00		0,204	25.00