


## POLYAMIDE CORRUGATED CONDUIT, DIVISIBLE



|      |       |        |
|------|-------|--------|
| IP54 | -40 C | +115 C |
|------|-------|--------|

### Технические характеристики



| Код продукта  | Размер I | A     | B     | C    | D      | E | Вес нетто (kg/м) | Количество в |
|---------------|----------|-------|-------|------|--------|---|------------------|--------------|
| <b>FDN008</b> | M12x1.5  | 8.00  | 13.00 | 2.50 | 75.00  |   | 0,048            | 50.00        |
| <b>FDN010</b> | M16x1.5  | 10.50 | 16.00 | 2.75 | 100.00 |   | 0,094            | 50.00        |
| <b>FDN014</b> | M20x1.5  | 13.90 | 21.00 | 3.55 | 120.00 |   | 0,111            | 50.00        |
| <b>FDN021</b> | M25x1.5  | 20.50 | 28.30 | 3.90 | 170.00 |   | 0,141            | 50.00        |
| <b>FDN027</b> | M32x1.5  | 26.60 | 34.50 | 3.95 | 180.00 |   | 0,216            | 25.00        |
| <b>FDN034</b> | M40x1.5  | 33.90 | 42.60 | 4.35 | 200.00 |   | 0,284            | 25.00        |
| <b>FDN045</b> | M50x1.5  | 45.10 | 54.50 | 4.70 | 240.00 |   | 0,321            | 25.00        |