




POLYAMIDE CORRUGATED CONDUIT, WIRE BRAIDED

| | | |
|------|-------|--------|
| IP55 | -40 C | +120 C |
|------|-------|--------|

Технические характеристики



| Код продукта | Размер I | A | B | C | D | E | Вес нетто (kg/м) | Количество в |
|--------------|----------|-------|-------|---|---|---|------------------|--------------|
| FNX007 | | 6.50 | 12.00 | | | | | 100.00 |
| FNX009 | | 8.50 | 14.00 | | | | | 100.00 |
| FNX010 | PG9 | 10.00 | 15.00 | | | | | 100.00 |
| FNX012 | PG11 | 12.00 | 17.00 | | | | | 50.00 |
| FNX014 | PG13.5 | 14.00 | 19.00 | | | | | 50.00 |
| FNX017 | PG16 | 16.50 | 23.00 | | | | | 50.00 |
| FNX023 | PG21 | 23.00 | 30.00 | | | | | 50.00 |
| FNX026 | | 26.00 | 33.00 | | | | | 25.00 |
| FNX029 | PG29 | 29.00 | 36.00 | | | | | 25.00 |
| FNX036 | PG36 | 36.00 | 44.00 | | | | | 25.00 |
| FNX048 | PG48 | 48.00 | 56.00 | | | | | 25.00 |